
P-0023A-01

X2335 TOW RKT MTR BOX

09-22-94

PART NAME: ROCKET MOTOR

SHIPPING CONTAINER: X2335, X2335-1, X2335-2

PACKING METHOD: PLACE PROTECTIVE CAP OVER GRAIN END OF MOTOR. PLACE ONE EACH (GRAIN UP) INTO A ANTI-STATIC PLASTIC BAG. CLOSE BAG WITH TWIST-EM. FOR P/N 13296390, PLACE SPACER, (1) PER CAVITY, INTO SHIPPING CONTAINER. PLACE (4) BAGGED PARTS INTO SHIPPING CONTAINER (1) PER CAVITY, GRAIN UP. PLACE 3/4" CORRUGATED FIBERBOARD PAD ON TOP. PLACE LID ON BOX AND SECURE WITH (2) 1/2" WIDE STRAPS AS INDICATED ON BOX. USE (8) EDGE PROTECTORS UNDER THE STRAPS AT EDGES.

MARKING INSTRUCTIONS: MARK AND LABEL CONTAINERS PER MIL-STD-129 AND DOT REQUIREMENTS.

SPECIAL INSTRUCTIONS: SHIPMENT SHALL BE IN ACCORDANCE WITH 49CFR.

PALLETIZATION INSTRUCTIONS: SHIPPING CONTAINERS MUST BE PALLETIZED USING X2473 PALLET (MAXIMUM OF 2 LAYERS OF 6 PER LAYER). USE 1/2" WIDE OR 3/4" WIDE STRAPS WITH EDGE PROTECTORS TO SECURE LOAD. INDIVIDUAL PALLETES MAY BE STACKED 2 HIGH FOR SHIPMENT.

NOTE: TO PRESERVE THE ENVIRONMENT, RAYTHEON CO. RECOMMENDS THAT PACKAGING MATERIALS WHICH ARE MANUFACTURED FROM, AND OR, WITH CFC'S (CHLOROFLOUROCARBONS) NOT BE USED.